



Triple-Tiller



50 Methven Highway, RD6, Ashburton, 7776
P: 03 307 7445 M: 027 782 7606
E: info@euroagri.co.nz www.euroagri.co.nz



EuroAgri
Importers of Machinery Excellence

HE-VA Triple-Tiller

- Stubble harrow with working widths of 3.00 m, 3.50 m, 4.00 m and 5.00 m



4.00 m trailed Triple-Tiller w/Ø600 mm V-Profile roller and eradicator discs.



3.00 m three-point mounted Triple-Tiller w/Ø600 mm V-Profile roller and levelling tines.



Unique tine, preloaded for 455 kg. 850 mm frame height, 750 mm tine spacing and 700 mm bar spacing. Row spacing 250 mm, 75 x 12 mm tine point and a max. working depth of 300 mm.

As extra equipment the "Quick change adapter" is available with chisel point or wing share.



◀ Adjustment of the working depth by means of distance clips.



▶ Spindle-adjustable levelling tines for levelling of tine tracks. Eradicator discs are available as extra equipment.



▶ Triple-Tiller shown with Ø600 mm V-Profile Roller. Triple-Tiller is also available with Ø550 mm Square Tube Roller or Ø600 mm T-Profile Roller.



▲ 2-sections models with hydr. folding ensure small transport width and easy and simple maintenance of the points.

 **HE-VA**

N. A. Christensensvej 34
DK-7900 Nykøbing Mors
Tel: +45 9772 4288
Fax: +45 9772 2112
www.he-va.com
info@he-va.com