

# FRONT-TANK



- Produced in materials that can handle fertilizer
- Standard with window and tarpaulin.
- Standard with hydraulic driven fan. Requires 35 l/min from oil outlet with flow control and return to sump without pressure.

## PRICES

Tank l.	Model	Item no.	
1100 l.	<b>** HE-VA Front-Tank</b> Manual adjustment of the seed rate	0537500	
1100 l.	<b>* HE-VA Front-Tank ISOBUS</b> (Speed signal is collected from the tractor)	0537610	
2000 l.	<b>** HE-VA Front-Tank</b> Manual adjustment of the seed rate	0537611	
2000 l.	<b>* HE-VA Front-Tank ISOBUS</b> (Speed signal is collected from the tractor)	0537612	
	Distributor heads with different number of outlets are available.	-	

\* Requires 1 double-acting oil outlet.

\*\* Requires 2 double-acting oil outlets.

## STANDARD EQUIPMENT

- Headlight with working light, tank light and direction indicator.
- Parking leg, loading platform and Cat. II three point linkage.
- Hydr. fan with 5 m firm tube and 10 m flexible tube for tractor mounting.
- Only Front-Tank mechanical:
  - Seed wheel with hydraulic lifting.
- Only Front-Tank ISOBUS:
  - Electronic control of the seed rate, monitoring, test turning etc.
- Only for Sub-Tiller:
  - Factory mounting on a new Sub-Tiller when adding a mounting set.

## SPECIFICATIONS

- 1100 l.: Length 1440 mm, width 2210 mm and operating height 1900 mm.
- 2000 l. Length 1440 mm, width 2210 mm and operating height 2200 mm