

TOP-STRIGLE



6,00 m Top-Strigle w/5 rows & 16 mm tines

- Hydraulic adjustment of working angle.
- Depth wheel placed at the rear of the Top-Strigle (not on 5-row models)
- Spindle adjustment of working depth.
- 12 mm long finger tines for aerating grasslands.
- 16 mm long finger tines for levelling of straw residues.

PRICES & SPECIFICATIONS

Working width	Mounted in front				Mounted behind			
	12 mm tines		16 mm tines		12 mm tines		16 mm tines	
	Item Number		Item - Number		Item Number		Item Number	
Top-Strigle, 2 bars:								
*3.00m rigid	67511-05		67512-05		67520-05		67522-05	
◆*4.00m rigid	67511-10		67512-10		67520-10		67522-10	
**4.00m hydr.	67511-15		67512-15		67520-15		67522-15	
**5.00m hydr.	67511-20		67512-20		67520-20		67522-20	
**6.00m hydr.	67511-25		67512-25		67520-25		67522-25	
**7.00m hydr.	67511-27		67512-27		67520-27		67522-27	
**8.00m hydr.	67511-30		67512-30		67520-30		67522-30	
Top-Strigle, 4 bars:								
*3.00m rigid	67514-05		67517-05		67524-05		67526-05	
◆*4.00m rigid	67514-10		67517-10		67524-10		67526-10	
**4.00m hydr.	67514-15		67517-15		67524-15		67526-15	
**5.00m hydr.	67514-20		67517-20		67524-20		67526-20	
**6.00m hydr.	67514-25		67517-25		67524-25		67526-25	
**7.00m hydr.	67514-27		67517-27		67524-27		67526-27	
**8.00m hydr.	67514-30		67517-30		67524-30		67526-30	
Top-Strigle, 5 bars:								
**3.00m rigid					67528-05		67518-05	
◆**4.00m rigid					67528-10		67518-10	
**4.00m hydr.					67528-15		67518-15	
**5.00m hydr.					67528-20		67518-20	
**6.00m hydr.					67528-25		67518-25	
**7.00m hydr.					67528-27		67518-27	
**8.00m hydr.					67528-30		67518-30	

* Requires 1 double-acting oil outlet.



** Requires 2 double-act oil outlets.


◆ 4.00 m with rigid frame, can manually be changed to 3.00 m transport width.


STANDARD EQUIPMENT FOR TOP-STRIGLE

- Wheel, 2 pcs.: 200/60x14.5 only on models with 2 and 4 rows.
- 2, 4 or 5 hydraulically adjustable tine rows with 12 or 16 mm long finger tines.
- The mutual angle between the tine rows is mechanically adjustable (not for models w/5 bars).
- Tine height of 12 mm: 44 cm
- Tine height of 16 mm: 66 cm
- Row spacing:
 - 2 bars with 12 mm long finger tines: 9.0 cm
 - 2 bars with 16 mm long finger tines: 12.5 cm
 - 4 bars with 12 mm long finger tines: 6.0 cm
 - 4 bars with 16 mm long finger tines: 8.3 cm
 - 5 bars with 12 mm long finger tines: 6.0 cm
 - 5 bars with 16 mm long finger tines: 8.3 cm
- Bar spacing:
 - On models with 2 bars: 400 mm
 - On models with 4 bars: 300 mm
 - On models with 5 bars: 500 mm

EXTRA EQUIPMENT

Designation		Weight	Item Number	DKK		
LED lights complete w/wire and socket		3	64509-01			
Weight console, f/bolting on of add. weight (not for models w/5 bars)		32 kg	67086-00	1.650		
Deduction for supply with spindle adjustment of working angle			67515-04			
Mounting set for Multi-Seeder. Max. 200 kg seeds in the seed hopper. Prices and info.about Multi-Seeder. page 98. 	Model	No of outlets	Without AC/EC		With AC/EC	
			Item Number		Item Number	
	3.00 m rigid	8 outlets	67515-10		67515-11	
	4.00 m rigid	8 outlets	67515-12		67515-13	
	4.00 m hydr.	8 outlets	67515-14		67515-15	
	5.00 m hydr.	8 outlets	67515-16		67515-17	
	5.00 m hydr.	16 outlets	67515-18		67515-19	
	6.00 m hydr.	8 outlets	67515-20		67515-21	
	6.00 m hydr.	16 outlets	67515-22		67515-23	
	7.00 m hydr.	16 outlets	67515-24		67515-25	
8.00 m hydr.	16 outlets	67515-26		67515-27		
Levelling bar with spindle height adjustment (not for models with 5 bars). 	Model	Weight kg	Item Number			
	3.00 m	100	67513-05			
	4.00 m	115	67513-10			
	5.00 m	130	67513-20			
	6.00 m	190	67513-25			
	7.00 m	205	67513-27			
Double three-point linkage: Hereby the Top-Strigle can be mounted both in front and in rear on the tractor.	3-4 m rigid (not for models with 5 bars)		67515-00			
	4-8 m hydr. (not for models with 5 bars)		67515-05			
Top-Cutter can be mounted, see page 50						

Extension set for 4,00 – 7,00 m. models with hydr. folding		Weight	Item no.
	2x75cm for 2-bullet Top-Strigle m/12 mm tænder	38 kg	67516-31
	2x75cm for 2-bullet Top-Strigle m/16 mm tænder	44 kg	67516-33
	2x75cm for 4-bullet Top-Strigle m/12 mm tænder	96 kg	67516-32
	2x75cm for 4-bullet Top-Strigle m/16 mm tænder	108 kg	67516-34
	2x75cm for 5-bullet Top-Strigle m/12 mm tænder	120 kg	67516-35
	2x75cm for 5-bullet Top-Strigle m/16 mm tænder	135 kg	67516-36

Turbo-Disc, Ø450 mm		Weight	Item no.
	Top-Strigle 3,00 w. rigid (only for 5-row models)	420	67411-01
	Top-Strigle 4,00 w. rigid (only for 5-row models)	520	67411-02
	Top-Strigle 4,00 w. hydr. (only for 5-row models)	530	67411-03
	Top-Strigle 5,00 w. hydr. (only for 5-row models)	680	67411-04
	Top-Strigle 6,00 w. hydr. (only for 5-row models)	840	67411-05
	Top-Strigle 7,00 w. hydr. (only for 5-row models)	940	67411-06
	Top-Strigle 8,00 w. hydr. (only for 5-row models)	1044	67411-07

SPECIFICATIONS

Working width and Type of tines 12 / 16 mm		Trans- port- width m	Height in trans- port position m	No of tines			Power Requirement HP			Weight kg		
				2 bars	4 bars	5 bars	2 bars	4 bars	5 bars	2 bars	4 bars	5 bars
3.00m rigid	12mm	3050	1500	33	50	50	75-100	85-110	85-110	340	790	840
	16mm	3050	1500	24	36	36	85-105	95-115	95-115	400	850	930
4.00m rigid	12mm	4050	1500	44	66	66	90-115	100-125	100-125	400	950	1060
	16mm	4050	1500	32	48	48	100-125	110-135	110-135	460	1050	1170
4.00m hydr.	12mm	1500	2100	44	66	66	90-115	100-125	100-125	650	1370	1480
	16mm	1500	2100	32	48	48	100-125	110-135	110-135	710	1480	1590
5.00m hydr.	12mm	1500	2600	55	82	82	105-130	120-145	120-145	750	1570	1660
	16mm	1500	2600	40	60	60	115-140	130-155	130-155	840	1660	1780
6.00m hydr.	12mm	1500	3100	66	100	100	120-150	140-170	140-170	860	1750	1840
	16mm	1500	3100	48	72	72	135-160	155-180	155-180	960	1850	1950
7.00m hydr.	12mm	1500	3600	78	116	116	140-175	160-195	160-195	990	1950	2020
	16mm	1500	3600	56	84	84	170-210	190-230	190-230	1100	2050	2150
8.00m hydr.	12mm	1500	3600	88	132	132	150-200	175-225	175-225	1120	2180	2240
	16mm	1500	3600	64	96	96	200-250	225-275	225-275	1240	2280	2390

